



TD-(565-585)T-144HC

MODULE SIZE

2279*1134*35mm

POWER OUTPUT RANGE

565W - 585W

POSITIVE POWER TOLERANCE

0 - + 3%

N-TOPCON MONOCRYSTALLINE MODULE



144 CELL

MAXIMUM EFFICIENCY

22.64%

LINEAR PERFORMANCE WARRANTY

15 Year Product Warranty
30 Year Linear Power Warranty



Competitive Low Light Performance



Reduced Power Loss by Minimising the Effect of Shadow Shading



High Density Encapsulation



Multi-Busbar Technology



2400pa Wind Load
5400pa Snow Load



Reduced BOS & Increased ROI

TIDE SOLAR


www.tide-solar.com

Add: Wind and Solar Industrial Park, Huishan, Wuxi, Jiangsu, China

Tel: +86-510-83885850

E-mail: info@tide-solar.com

DIMENSIONS OF PV MODULE



STRUCTURAL CHARACTERISTICS

Module Size	2279x1134x35mm
Weight	25kg
Cell	single crystal N-topcon 182x91mm(144pieces)
Glass	3.2mm tempered coated glass, low iron
Frame	anodized aluminum alloy
Junction Box	IP68, 3 diodes
Output Lead	4.0mm ² 300mm(+)/ 300mm(-) or customized
Mechanical Load	front 5400pa / back 2400pa

ELECTRICAL CHARACTERISTICS

Component Model	TD-565T-144HC	TD-570T-144HC	TD-575T-144HC	TD-580T-144HC	TD-585T-144HC
Maximum Power (PMP)	STC	STC	STC	STC	STC
	565	570	575	580	585
Open Circuit Voltage (VOC)	50.60	50.74	50.88	51.02	51.16
Short Circuit Current (ISC)	14.23	14.31	14.39	14.47	14.55
Maximum Power Voltage (VMP)	41.92	42.07	42.22	42.37	42.52
Maximum Power Current (IMP)	13.48	13.55	13.62	13.69	13.76
Component Efficiency (η)	21.86	22.06	22.25	22.44	22.64
Power Tolerance	(0, +3%)				
Maximum System Voltage	1500V DC				
Maximum Rated Fuse Current	25A				
STC: Irradiance 1000 W/m² module temperature 25 °C AM=1.5					

TEMPERATURE CHARACTERISTICS

Maximum Power Temperature Coefficient	-0.30 % / °C
Temperature Coefficient Of Open Circuit Voltage	-0.25 % / °C
Temperature Coefficient Of Short Circuit Current	+0.046 % / °C
Working Temperature	-40 ~ +85 °C
Nominal Operating Cell Temperature (NOCT)	45 ± 2 °C

PACKING METHOD

Module Size	2279x1134x35mm
Container	40' HQ
Quantity Per Pallet	31
Number Of Pallets Per Container	20
Quantity Per Container	620

I-V Curve

